



= RECOMMENDED FOR MAINTENANCE, REQUIRED FOR COVERS



SPECIFICATIONS & OPTIONS

OPENING SIZE	W=	H=
MFG. DOOR SIZE	W=	H=
PRIMARY VOLTAGE	208-240	440-480 575-600
DRIVE SIDE - (RH / LH)		OPERATOR SPEED (1/2)
CONTROL PANEL (ACS 50 / PLC)		SPRINGS YES
		F.R. COVERS (YES / NO)
WINDBAR (FRONT / REAR / NO)		
WINDOWS (QTY.) DETERMINED BY MFG. DOOR WIDTH		
FABRIC (BLACK SBR / GRAY EPDM / BLUE EPDM)		
DOOR ACTUATORS (QUANTITY)	PUSHBUTTON	<901>
	PULL SWITCH	<911>
	FLOOR LOOP	<930>
	PHOTOCELLS THRU BEAM	<940>
	REFLECTIVE	<941>
	MOTION DETECTOR	<950>
	RADIO RECEIVER	<925>

COMMENTS:

BALANCED OVER 12'-0" X 12'-0"
SPRINGLESS OVER 391 SQ. FT.
(SPEED ZONE #1, #2, #3, #4, #5, #6, #7, #8, AND #12)

CUSTOMER:	APPROVED BY:					
LOCATION:	APPROVED WITH CHANGES BY:					
SALESMAN / DEALER:	DATE: SCALE = N.T.S.					
DESCRIPTION:		ULTRA TOUGH APPROVAL				
Rev	Change	Date	Name	DRAWING NO: ULTRA TOUGH-003	DESIGNER: J. REITZ	DATE: 12/07/2007